RUGGED COMPACT LIGHTWEIGHT

- IP68 up to 120 m / IP69 / Hermetic
- 360° EMC shielding
- **■** High corrosion resistance
- 10,000 mating cycles

















BODY **STYLES**





07 (2 – 10 contacts)



08 (2 – 9 contacts)



11 (8 – 19 contacts)



13 (5 – 27 contacts)



15 (2 – 27 contacts)



*Actual size 1:1 when printed at full size on A4 paper.

RESINATED CONTACT BLOCK

- Better sealing (IP68/69 even unmated, gas-tight, NBCR decontamination)
- Greater shock and vibration resistance
- Superior cable resistance (traction)

PLUGS**

CABLE MOUNTED

Design



BODY STYLES	UP01-L	
Locking system	Push-pull	
Sealing	IP68/IP69	
Design	Short/Overmolding	



Quick-release IP68/IP69 Short/Overmolding

PANEL FRONT MOUNTED



BODY STYLES	
ocking system	
Sealing	
Design	F

UP50	
Non-locking	
IP68/IP69	
Front-projecting	

RECEPTACLES**

CABLE MOUNTED



BODY STYLES
Sealing
Design

IP68 / IP69 Standard

PANEL FRONT MOUNTED



BODY STYLES	
Sealing	
Design	

	UR	UR03		
	IP68/IP69	Hermeti		
Front-projecting				

PANEL REAR MOUNTED

BODY STYLES Sealing

Design





IP68/IP69 Hermetic IP68/IP69 Hermetic Front-projecting Rear-projecting

BEND RELIEF & CABLE ASSEMBLY

- Bend relief for easy self-assembly, no tool required
- Cable assembly with straight or angled overmolding
- 120 m submersible solution available on request











^{**} Available in brass and aluminum. Available in anthracite and chrome grey finish.